

VISION®

标准型008/009型

1 产品描述

1.1 规格

- DN50-300

1.2 管道

- GB/T 3091 《低压流体输送用焊接钢管》
- GB/T 9163 《输送流体用无缝钢管》
- GB/T 17395 《无缝钢管尺寸、外形、重量及允许偏差》

1.3 最大工作压力

- 工作压力等同于LIGID及001型接头
- 认证压力: 2.5MPa

1.4 功能

- 用于连接管道，实现管径及连接方式转换。

2 认证



3 部件材质

3.1 外壳: 球墨铸铁, 满足 GB/T 1348, 牌号QT450-12

3.2 表面涂层 (确定选项)

- 环氧树脂喷粉, 消防红 RAL3000
- 热镀锌




008 | 同心大小头-沟槽/沟槽

规格 mm		EE	约重
公称直径	实际外径	mm	kg
80 x 50	88.9 x 60.3	64	0.5
	76.1	64	0.6
100 x 50	108.0 x 60.3	76	0.8
	76.1	76	0.8
	88.9	76	0.8
100 x 50	114.3 x 60.3	76	0.8
	76.1	76	0.9
	88.9	76	0.9
125 x 50	139.7 x 60.3	89	1.2
	76.1	89	1.2
	88.9	89	1.2
	114.3	89	1.3
150 x 50	159.0 x 60.3	102	1.6
	76.1	102	1.7
	88.9	102	1.7
	108.0	102	1.8
	114.3	102	1.8
150 x 50	165.1 x 60.3	102	1.6
	76.1	102	1.7
	88.9	102	1.7
	114.3	102	1.8
	219.1 x 60.3	127	2.9
200 x 50	76.1	127	2.9
	88.9	127	3.0
	108.0	127	3.1
	114.3	127	3.1
	159.0	127	3.2
	165.1	127	3.3
250 x 150	273.0 x 159.0	152	5.4
	165.1	152	5.4
	219.1	152	5.8
300 x 150	323.9 x 159.0	178	8.4
	165.1	178	8.5
	219.1	178	8.7
	273.0	178	9.2

• 更多规格及信息, 请咨询上海威逊。



VISION®
标准型008/009型



009型

009 | 同心大小头-沟槽/内螺纹

规格 mm		EE	约重
公称直径	实际外径	mm	kg
50 x 25	60.3 x 33.7	64	0.3
		64	0.3
		64	0.4
65 x 25	76.1 x 33.7	64	0.4
		64	0.4
		64	0.5
		64	0.5
80 x 25	88.9 x 33.7	64	0.5
		64	0.5
		64	0.5
		64	0.6
		64	0.7
100 x 25	108.0 x 33.7	76	0.7
		76	0.7
		76	0.7
		76	0.8
		76	0.8
100 x 25	114.3 x 33.7	76	0.8
		76	0.8
		76	0.8
		76	0.9
		76	0.9
125 x 25	139.7 x 33.7	89	1.1
		89	1.1
		89	1.1
		89	1.2
		89	1.2
150 x 25	159.0 x 33.7	102	1.5
		102	1.5
		102	1.5
		102	1.6
		102	1.6
150 x 25	165.1 x 33.7	102	1.7
		102	1.8
		102	1.8
		102	1.8
		102	1.8

